



HIGH PERFORMANCE THROTTLE BODY INSTALLATION INSTRUCTIONS

Part Number: D760-3250A

Applications: 2001-04 325i/ci/xi
2001-03 525i
2001-02 Z3 2.5i
2003-05 Z4 2.5i
2004-05 X3 2.5

PARTS LIST

	Dinan Throttle Body
	Profile Gasket
	Dipstick Tube Seal

Please Note:

- Some mechanical skill is required to install this throttle body. Proper installation of this throttle body also requires complete understanding of the recommended BMW throttle body removal procedure for your vehicle. If you are not familiar with this BMW procedure, we strongly recommend that you arrange for a qualified BMW repair facility to perform this installation.

If you encounter any difficulties during installation, or if these instructions are not clear to you, please call Dinan Engineering's Technical Support Staff @ (408) 779-8584.

INSTALLATION:

- I. Remove the original throttle body following recommended BMW procedure for throttle body removal.

2. The installation of the Dinan Engineering High Performance Throttle Body is simply the reverse of removal. Please take note to:
 - Replace the profile gasket.
 - Replace the dipstick tube seal (E46 only).
 - Reset DME adaptations using the BMW DIS or Dinan MIPP. Please be aware that the vehicle may exhibit abnormal drivability symptoms immediately after adaptations are cleared. Allowing the DME the opportunity to “relearn” can restore normal drivability.

NOTES:

- For best results, we recommend that this throttle body be used with the appropriate Dinan software for your vehicle. Please contact your Dinan representative for details.